




Typical Features

- ◆ Wide input voltage range: 85-265VAC/120-380VDC
- ◆ No load power consumption ≤ 0.45W
- ◆ Transfer Efficiency 86%(TYP.)
- ◆ Switching Frequency: 65KHz
- ◆ Protections: short circuit, over current
- ◆ Isolation voltage: 3000Vac
- ◆ Conform to IEC60950/UL60950/EN60950 test Standard
- ◆ PCB mounting



Application Field

DA60-220SXXG2N3 Series----- a compact size, high efficient power module offered by Aipu. It features universal input voltage range, AC and DC dual-use, low ripple, low temperature rise, low power consumption, high efficiency, high reliability, safer isolation, good EMC performance, For EMC and safety spec conform to EN55032, IEC/EN61000 standard. These series have important application for power, industry, instrument and smart home field. For harsh EMC environment, the application circuit in the datasheet is strongly recommended.

Typical Product List

Certificate	Part No.	Output Specifications					Max. Capacitive Load	Ripple & Noise 20MHz (Max)	Efficiency@ Full Load, 220Vac (Typical)
		Power	Voltage1	Current1	Voltage 2	Current 2			
		(W)	Vo1(V)	Io1(mA)	Vo2(V)	Io2(mA)			
-	DA60-220S12G2N3	60	12	5000	-	-	6000	120	86
-	DA60-220S48G2N3	60	48	1250	-	-	600	150	88

Note 1: "*" are models being developing.
 Note 2: The typical value of output efficiency is based on module is full loaded and burned-in after half an hour.
 Note 3: The fluctuation range of full load efficiency(% ,TYP) in table is ±2%, full load efficiency= output power/module's input power.

Input Specifications

Item	Operating Condition	Min	Typ.	Max	Unit
Input Voltage Range	AC input	85	220	265	VAC
	DC input	120	310	380	VDC
Input Frequency range	-	47	50	63	Hz
Input Current	115VAC	/	/	1.2	A
	220VAC	/	/	0.66	
Surge Current	115VAC	/	/	10	
	220VAC	/	/	20	



Leakage Current	-	0.5mA TYP/230VAC/50Hz
Recommended External Input Fuse	-	3.15A/250VAC slow fusing
Hot Plug	-	Unavailable
Remote Control Terminal	-	Unavailable

Output Specifications

Item	Operating Condition	Min	Typ.	Max	Unit
Voltage Accuracy	Full input voltage range, any load	-	±2.0	±3.0	%
Line Regulation	Nominal load	-		±0.5	%
Load Regulation	Nominal input voltage, 20%~100% load			±1.0	%
No Load Power Consumption	Input 115VAC	-	-	0.45	W
	Input 220VAC	-	-		
Minimum Load	Single Output	0	-	-	%
	Dual output common ground	-	-	-	%
	Dual output but Isolated	-	-	-	
Start up Delay Time	Nominal input voltage (full load)	-	1500	-	mS
Power-off Holding Time	Input 115VAC (full load)	-	200	-	mS
	Input 220VAC (full load)	-	100	-	
Dynamic Response	25%~50%~25% 50%~75%~50%	Overshoot range(%)≤±5.0			%
		Recovery time(mS)≤5.0			mS
Output Overshoot	Full input voltage range	≤10%Vo			%
Short circuit Protection		Continuous, self-recovery			Hiccup
Temperature Drift	-	-	±0.03%	-	%/°C
Over Current Protection	Full input voltage range	≥130% Io, self-recovery			Hiccup

General Specifications

Item	Operating Condition	Min	Typ.	Max	Unit
Switching Frequency	-	-	65	-	KHz




Operating Temperature	-	-40	-	+75	°C
Storage Temperature	-	-40	-	+85	
Soldering Temperature	Wave soldering	260±4°C, time 5-10S			
	Manual soldering	360±8°C, time 4-7S			
Relative Humidity	-	10	-	90	%RH
Isolation Voltage	Input-Output, Test 1min, leakage current≤5mA	3000	-	-	VAC
Insulation Resistance	Input-Output@ DC500V	100	-	-	MΩ
Safety Standard	-	EN60950, IEC60950			
Vibration	-	10-55Hz,10G,30Min,alongX,Y,Z			
Safety Class	-	CLASS II			
MTBF	-	MIL-HDBK-217F@25°C > 300,000H			
Cooling Method	-	Free air convection			

EMC Characteristics

Total Item		Sub Item	Test Standard	Class
EM C	EMI	CE	CISPR22/EN55032	CLASS B (See Recommended Circuit on photo 2)
		RE	CISPR22/EN55032	CLASS B (See Recommended Circuit on photo 2)
	EMS	RS	IEC/EN61000-4-3	10V/m Perf.Criteria B (See Recommended Circuit on photo 1)
		CS	IEC/EN61000-4-6	3Vr.m.s Perf.Criteria B (See Recommended Circuit on photo 1)
		ESD	IEC/EN61000-4-2	Contact ±6KV/ Air ±8KV Perf.Criteria B
		Surge	IEC/EN61000-4-5	±1KV Perf.Criteria B
		EFT	IEC/EN61000-4-4	±2KV Perf.Criteria B
		Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11	0%~70% Perf.Criteria B

Dimension



Packing Code	L x W x H	
-	84 x 49 x 27.5 mm	3.307 × 1.929 × 1.082 inch

Pin Specification

Pin	1	2	3	4
Single(S)	AC(N)	AC(L)	V-	V+


Note: If the definition of pin is not in accordance with the model selection manual, please refer to the label on actual item.

Ripple & Noise Test: (Twisted Pair Method 20MHz bandwidth)


Test Method:

(1) 12# twisted pair to connect, Oscilloscope bandwidth set as 20MHz, 100M bandwidth probe, terminated with 0.1uF polypropylene capacitor and 10uF high frequency low resistance electrolytic capacitor in parallel, oscilloscope set as Sample pattern.

(2) Input terminal connect to power supply, output terminal connect to electronic load through jig plate, Use 30cm±2 cm sampling line, Power line selected from corresponding diameter wire with insulation according to the flow of output current.




Product Characteristic Curve



Note 1: Input Voltage should be derated based on Input voltage derating curve when it is 85~100VAC/240~265VAC/120~140VDC/340~380VDC.

Note 2: Our product is suitable to use under natural air cooling environment, if use it under closed condition, please contact with us.

Typical Application Circuit and EMC Recommended Circuit





NOTE 1:

1. Output filter capacitor C1 filters high frequency noise, recommended 1 μ F ceramic capacitor, capacitor withstand voltage derating > 80%.
2. TVS is recommended to use to protect post circuit (when module is abnormal), recommend 600W model.
5V output: SMBJ7.0A, 9V output: SMBJ12.0A, 12V output : SMBJ20A, 15V output: SMBJ20.0A, 24V output: SMBJ30.0A, 48V output: SMBJ64A.
3. MOV is voltage dependent resistor, recommend model 10D561K, to protect module from lightning surge.
4. For general application requirements, customers could use recommended circuit Photo 1, If has higher EMC requirement, Photo 2 circuit is recommended, The specific for Photo 2:
 - 1) Varistor MOV: recommended 10D-561K, to protect module from lightning surge.
 - 2) Thermistor NTC: 10D-9.
 - 3) Safety capacitor CY1, CY2: 1000pF/400VAC.
 - 4) Safety capacitor CX: 0.1 μ F/275VAC.
 - 5) Common mode inductor LCM: 15mH-30mH.
 - 6) FUSE: necessary, recommend model 3.15A/250V, slow fusing.

Note 2:

1. The product should be used within the specification range, or it will cause permanent damage to it;
2. The input terminal should connect to fuse;
3. If the product is worked under the minimum requested load, the product performance cannot be guaranteed to comply with all parameters in the datasheet;
4. If the product is not operated within the required load range, the product performance cannot be guaranteed to comply with all parameters in the datasheet;
5. Unless otherwise specified, parameters in this datasheet were measured under the conditions of **Ta=25°C**, **humidity<75%** with nominal input voltage and rated output load(pure resistance load);
6. All index testing methods in this datasheet are based on our Company's corporate standards;
7. The performance indexes of the product models listed in this manual are as above, but some indexes of non-standard model products will exceed the above-mentioned requirements, please directly contact our technician for specific information;
8. We can provide product customization service,
9. Specifications are subject to change without prior notice, please follow up with our website for newest manual.