



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- $\pm 10\%$

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M3/min	CFM	MmH2O	IN H2O	dB-A
K-DC2510-A5-52H	5	4~6	0.06	0.3	5200	0.025	0.92	1.24	0.054	18.5
K-DC2510-A5-72H			0.09	0.45	7200	0.036	1.33	2.94	0.106	20
K-DC2510-A5-10H			0.13	0.65	10000	0.05	1.8	4.45	0.174	23.5
K-DC2510-A5-130H			0.2	1.0	13000	0.066	2.35	7.62	0.298	28
K-DC2510-A12-52H	12	9~13	0.04	0.48	5200	0.025	0.92	1.24	0.054	18.5
K-DC2510-A12-72H			0.06	0.72	7200	0.036	1.33	2.94	0.106	20
K-DC2510-A12-100H			0.08	0.96	10000	0.05	1.8	4.45	0.174	23.5
K-DC2510-A12-130H			0.1	1.2	13000	0.066	2.35	7.62	0.298	28

