



- Material--Frame:Plastics (Flammability:UL94V-0)  
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black  
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range--  $\pm 10\%$

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt		M <sup>3</sup> /min	CFM	MmH2O	IN H2O	
K-DC3010-A5-60H	5	4~6	0.08	0.4	6000	0.067	2.36	1.02	0.042	17.5
K-DC3010-A5-80H			0.13	0.6	8000	0.089	3.18	1.63	0.073	21
K-DC3010-A5-100H			0.2	1.0	10000	0.11	3.65	2.62	0.115	25.5
K-DC3010-A12-60H	12	9~13	0.04	0.48	6000	0.067	2.36	1.02	0.042	17.5
K-DC3010-A12-80H			0.08	0.72	8000	0.089	3.18	1.63	0.073	21
K-DC3010-A12-100H			0.1	0.96	10000	0.11	3.65	2.62	0.115	25.5

