



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- $\pm 10\%$

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M ³ /min	CFM	MmH ₂ O	IN H ₂ O	dB-A
K-DC3510-A5-44H	5	4~6	0.06	0.30	4400	0.092	3.30	1.19	0.045	15.5
K-DC3510-A5-57H			0.10	0.50	5700	0.126	4.48	1.88	0.073	18
K-DC3510-A5-70H			0.14	0.60	7000	0.153	5.46	2.65	0.102	22.5
K-DC3510-A12-44H	12	9~13	0.03	0.36	4400	0.092	3.30	1.19	0.045	15.5
K-DC3510-A12-57H			0.05	0.60	5700	0.126	4.48	1.88	0.073	18
K-DC3510-A12-70H			0.09	1.08	7000	0.153	5.46	2.65	0.102	22.5

