



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-comdensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M³/min	CFM	MmH2O	IN H2O	dB-A
K-DC3628-A12-140H	12	9.5~13.2	0.35	4.2	14000	0.4	14.08	28.04	1.104	52
K-DC3628-A12-190H			0.75	9.0	19000	0.55	19.36	53.34	2.1	58
K-DC3628-A12-240H			1.3	15.6	24000	0.69	24.29	85.3	3.36	66
K-DC3628-A24-140H	24	13.5~26	0.175	4.2	14000	0.4	14.08	28.04	1.104	52
K-DC3628-A24-190H			0.375	9.0	19000	0.55	19.36	53.34	2.1	58
K-DC3628-A24-240H			0.55	15.6	24000	0.69	24.29	85.3	3.36	66

