



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M³/min	CFM	MmH2O	IN H2O	dB-A
K-DC4015-A12-49H	12	7~13.2	0.06	0.72	4900	0.181	6.42	3.62	0.141	19
K-DC4015-A12-59H			0.09	1.08	5900	0.220	8.08	5.09	0.198	25.5
K-DC4015-A12-69H			0.10	1.2	6900	0.263	9.38	6.86	0.268	29
K-DC4015-A12-82H			0.13	1.56	8200	0.316	11.28	9.08	0.351	32.5
K-DC4015-A12-93H			0.16	1.92	9300	0.360	12.89	11.52	0.453	37.5
K-DC4015-A12-100H			0.25	3.00	10500	0.411	14.65	14.98	0.592	42.5
K-DC4015-A24-49H	24	14.5~26.5	0.05	1.20	4900	0.181	6.42	3.62	0.141	19
K-DC4015-A24-59H			0.06	1.44	5900	0.220	8.08	5.09	0.198	25.5
K-DC4015-A24-69H			0.08	1.92	6900	0.263	9.38	6.86	0.268	29
K-DC4015-A24-82H			0.09	2.16	8200	0.316	11.28	9.08	0.351	32.5
K-DC4015-A24-93H			0.1	2.40	9300	0.360	12.89	11.52	0.453	37.5
K-DC4015-A24-100H			0.12	2.88	10500	0.411	14.65	14.98	0.592	42.5

