



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Rated Input	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M³/min	CFM	MmH2O	In H2O	dB-A
K-DC4028-A12-125H	12	9.5~13.2	0.24	2.88	12500	0.46	16.2	26.4	1.04	47
K-DC4028-A12-145H			0.29	3.48	14500	0.54	19.1	35.3	1.39	50
K-DC4028-A12-165H			0.46	5.52	16500	0.61	21.5	45.9	1.81	53.5
K-DC4028-A12-180H			0.6	7.2	18000	0.67	23.7	54.6	2.15	55
K-DC4028-A24-220H			1.1	13.2	22000	0.81	28.6	81.5	3.21	61
K-DC4028-A24-125H	24	13.5~26	0.12	2.88	12500	0.46	16.2	26.4	1.04	47
K-DC4028-A24-145H			0.145	3.48	14500	0.54	19.1	35.3	1.39	50
K-DC4028-A24-165H			0.23	5.52	16500	0.61	21.5	45.9	1.81	53.5
K-DC4028-A24-180H			0.3	7.2	18000	0.67	23.7	54.6	2.15	55
K-DC4028-A24-220H			0.55	13.2	22000	0.81	28.6	81.5	3.21	61

