



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M3/min	CFM	MmH2O	IN H2O	dB-A
K-DC4028-A5-49H	5	4~6.5	0.09	0.45	4900	0.215	7.92	3.65	0.142	24.5
K-DC4028-A5-64H			0.11	0.55	6400	0.292	10.12	6.21	0.232	33.5
K-DC4028-A12-49H	12	9.5~13.2	0.06	0.72	4900	0.215	7.92	3.65	0.142	24.5
K-DC4028-A12-64H			0.08	0.96	6400	0.292	10.12	6.21	0.232	33.5
K-DC4028-A12-79H			0.13	1.56	7900	0.361	12.98	9.18	0.348	38.5
K-DC4028-A12-92H			0.17	2.04	9200	0.436	15.24	12.75	0.499	43
K-DC4028-A12-110H			0.4	4.80	11000	0.637	20.42	19.1	0.758	49
K-DC4028-A12-130H			0.7	8.4	13000	0.687	25.42	26.1	1.058	49
K-DC4028-A24-49H			24	13.5~26	0.05	1.2	4900	0.215	7.92	3.65
K-DC4028-A24-64H	0.07	1.68			6400	0.292	10.12	6.21	0.232	33.5
K-DC4028-A24-79H	0.09	2.16			7900	0.361	12.98	9.18	0.348	38.5
K-DC4028-A24-92H	0.11	2.64			9200	0.436	15.24	12.75	0.499	43

