



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

Model No.	Rated Voltage	Operating Voltage	Rated Current	Rated Input	Speed	Maximum Air Flow		Max.Static Pressure		Noise
	VDC	VDC	AMP	Watt	R.P.M	M3/min	CFM	MmH2O	IN H2O	dB-A
K-DC5010-A5-34H	5	4~6.5	0.075	0.375	3400	0.210	7.45	1.68	0.065	18
K-DC5010-A5-44H			0.14	0.6	4400	0.258	9.17	2.82	0.109	25
K-DC5010-A5-54H			0.21	1.05	5400	0.320	11.35	4.21	0.163	30.5
K-DC5010-A12-34H	12	7.5~13.2	0.055	0.66	3400	0.210	7.45	1.68	0.065	18
K-DC5010-A12-44H			0.09	1.08	4400	0.258	9.17	2.82	0.109	25
K-DC5010-A12-54H			0.11	1.32	5400	0.320	11.35	4.21	0.163	30.5
K-DC5010-A12-64H			0.16	1.92	6400	0.380	13.48	5.83	0.228	35

