



- Material--Frame:Plastics (Flammability:UL94V-0)
Impeller:Plastics (Flammability:UL94V-0)
- Lead Wire-- +Red -Black
Optional Function:Brown(Sensor) Yellow(Control)
- Storage Temperature-- -30°C~+70°C (Non-condensing)
- Bearing Type-- Ball Bearings~Sleeve
- Speed Range-- ±10%

| Model No. | Rated Voltage | Operating Voltage | Rated Current | Rated Input | Speed | Maximum Air Flow | | Max.Static Pressure | | Noise |
|------------------|---------------|-------------------|---------------|-------------|-------|------------------|-------|---------------------|--------|-------|
| | VDC | VDC | AMP | Watt | | M3/min | CFM | MmH2O | IN H2O | |
| K-DC5015-A5-39H | 5 | 4~6.5 | 0.16 | 0.8 | 3900 | 0.27 | 9.82 | 3.12 | 0.121 | 24.5 |
| K-DC5015-A5-47H | | | 0.23 | 1.15 | 4700 | 0.346 | 12.31 | 4.52 | 0.176 | 28.5 |
| K-DC5015-A5-55H | | | 0.33 | 1.65 | 5500 | 0.394 | 14.02 | 6.01 | 0.232 | 32.5 |
| K-DC5015-A12-39H | 12 | 7.5~13.2 | 0.07 | 0.84 | 3900 | 0.27 | 9.82 | 3.12 | 0.121 | 24.5 |
| K-DC5015-A12-47H | | | 0.09 | 1.08 | 4700 | 0.346 | 12.31 | 4.52 | 0.176 | 28.5 |
| K-DC5015-A12-55H | | | 0.11 | 1.32 | 5500 | 0.394 | 14.02 | 6.01 | 0.232 | 32.5 |
| K-DC5015-A12-63H | | | 0.14 | 1.68 | 6300 | 0.453 | 16.02 | 7.89 | 0.304 | 37 |
| K-DC5015-A24-39H | 24 | 14.5~26 | 0.06 | 1.44 | 3900 | 0.27 | 9.82 | 3.12 | 0.121 | 24.5 |
| K-DC5015-A24-47H | | | 0.07 | 1.68 | 4700 | 0.346 | 12.31 | 4.52 | 0.176 | 28.5 |
| K-DC5015-A24-55H | | | 0.08 | 1.92 | 5500 | 0.394 | 14.02 | 6.01 | 0.232 | 32.5 |
| K-DC5015-A24-63H | | | 0.09 | 2.16 | 6300 | 0.453 | 16.02 | 7.89 | 0.304 | 37 |

